

RESPONSE
SN 09/525,696
PAGE - 2 of 13 -

IN THE CLAIMS

Please cancel claim 3.

Please rewrite claims 1, 28, 37, and 40.

1. (Currently Amended) A method for generating a pulse code modulated (PCM) signal stream from a plurality of streamed packets received over a packet network, said method comprising the steps of:

decoding said plurality of streamed packets to generate a decoded signal stream;

[[and]]

filtering said decoded signal stream to generate said PCM signal stream; and
rate converting said PCM signal stream.

2. (Original) The method of claim 1 wherein said step of filtering utilizes a low pass filter.

3. Cancelled.

4. (Original) The method of claim 3 further comprising the step of launching said PCM signal stream for transmission over a circuit switched network.

5. (Original) The method of claim 4 wherein said circuit switched network is a cellular network.

6. (Original) The method of claim 5 wherein said packet network is an IP based network.

7. (Original) The method of claim 6 wherein said PCM signal stream is a media signal stream.

8. (Original) The method of claim 7 wherein said media signal stream is an audio signal stream.

RESPONSE
SN 09/525,696
PAGE - 3 of 13 -

9. (Original) The method of claim 7 wherein said media signal stream is a video signal stream.
10. (Original) The method of claim 7 wherein said media signal stream is a text signal stream.
11. (Original) The method of claim 5 wherein said packet network is the Internet.
12. (Original) A method for generating a pulse code modulated (PCM) streamed audio signal from a plurality of streamed packets received from an Internet content provider server over the Internet, said PCM streamed audio signal suitable for conveyance over a circuit switched call connection, said method comprising the steps of:
- receiving said plurality of streamed packets;
 - decoding said plurality of streamed packets to generate a decoded signal stream;
 - converting the bit rate of said decoded signal stream to generate a converted signal stream compatible with said circuit switched call connection; and
 - filtering said converted signal stream to generate said PCM streamed audio signal.
13. (Original) The method of claim 12 wherein said circuit switched call connection is provided over a wireless network.
14. (Original) The method of claim 13 wherein said wireless network is a cellular network.
15. (Original) The method of claim 14 wherein said cellular network is a time division multiple access (TDMA) network.

RESPONSE
SN 09/525,696
PAGE - 4 of 13 -

16. (Original) The method of claim 14 wherein said cellular network is a code division multiple access (CDMA) network.

17. (Original) The method of claim 14 wherein said cellular network is a Groupe Speciale Mobile (GSM) network.

18. (Original) An apparatus for generating a pulse code modulated (PCM) streamed audio signal from a plurality of streamed packets received from an Internet content provider server over the Internet, said PCM streamed audio signal suitable for conveyance over a circuit switched call connection, said apparatus comprising:
 means for receiving said plurality of streamed packets;
 means for decoding said plurality of streamed packets to generate a decoded signal stream;
 means for converting the bit rate of said decoded signal stream to generate a converted signal stream compatible with said circuit switched call connection; and
 means for filtering said converted signal stream to generate said PCM streamed audio signal.

19. (Original) The apparatus of claim 18 wherein said circuit switched call connection is provided over a wireless network.

20. (Original) The apparatus of claim 19 wherein said wireless network is a cellular network.

21. (Original) An apparatus for generating a pulse code modulated (PCM) streamed audio signal from a plurality of streamed packets received from an Internet content provider server over the Internet, said PCM streamed audio signal suitable for conveyance over a circuit switched call connection, said apparatus comprising:
 a packet interface for receiving said plurality of streamed packets;

RESPONSE
SN 09/525,696
PAGE - 5 of 13 -

a decoder for decoding said plurality of streamed packets to generate a decoded signal stream;

a rate converter for converting the bit rate of said decoded signal stream to generate a converted signal stream compatible with said circuit switched call connection; and

a filter for filtering said converted signal stream to generate said PCM streamed audio signal.

22. (Original) The apparatus of claim 21 wherein said rate converter converts the bit rate of said decoded signal stream to 64 kbps.

23. (Original) The apparatus of claim 21 wherein said circuit switched call connection is provided over a wireless network.

24. (Original) The apparatus of claim 23 wherein said wireless network is a cellular network.

25. (Original) The apparatus of claim 21 wherein said filter is a low pass filter.

26. (Original) The apparatus of claim 25 wherein said low pass filter is utilized to prevent aliasing.

27. (Original) An apparatus for generating a pulse code modulated (PCM) streamed audio signal from a plurality of streamed packets received from an Internet content provider server over the Internet, said PCM streamed audio signal suitable for conveyance over a circuit switched call connection, said apparatus comprising:

a packet interface for receiving said plurality of streamed packets;

a processor; and

a memory coupled to said processor and including instructions for controlling said processor.

RESPONSE
SN 09/525,696
PAGE - 6 of 13 -

said processor operative with said instructions in said memory to;
decode said plurality of streamed packets to generate a decoded signal stream;
convert the bit rate of said decoded signal stream to generate a converted signal stream compatible with said circuit switched call connection; and
filter said converted signal stream to generate said PCM streamed audio signal.

28. (Currently Amended) An apparatus for generating a pulse code modulated (PCM) signal stream from a plurality of streamed packets received over a packet network, said apparatus comprising:

means for decoding said plurality of streamed packets to generate a decoded signal stream; [[and]]

means for filtering said decoded signal stream to generate said PCM signal stream;

means for rate converting said PCM signal stream.

29. Cancelled.

30. (Original) The apparatus of claim 28 further comprising a switched circuit interface for transmitting said PCM signal stream over a circuit switched call connection.

31. (Original) The apparatus of claim 28 wherein said packet network is an IP based network.

32. (Original) The apparatus of claim 28 wherein said packet network is the Internet.

33. (Original) The apparatus of claim 28 wherein said PCM signal stream is a media signal stream.

34. (Original) The apparatus of claim 33 wherein said media signal stream is an audio signal stream.

RESPONSE
SN 09/525,696
PAGE - 7 of 13 -

35. (Original) The apparatus of claim 33 wherein said media signal stream is a video signal stream.

36. (Original) The apparatus of claim 33 wherein said media signal stream is streaming text.

37. (Currently Amended) An apparatus for generating a pulse code modulated (PCM) signal stream from a plurality of streamed packets received over a packet network, said apparatus comprising:

a decoder for decoding said plurality of streamed packets to generate a decoded signal stream; [[and]]

a filter for filtering said decoded signal stream to generate said PCM signal stream;

a rate converter for rate converting said PCM signal stream.

38. (Original) The apparatus of claim 37 wherein said filter is a low pass filter.

39. (Original) The apparatus of claim 38 wherein said low pass filter is utilized to prevent aliasing.

40. (Currently Amended) An apparatus for generating a pulse code modulated (PCM) signal stream from a plurality of streamed packets received over a packet network, said apparatus comprising:

a processor; and

a memory coupled to said processor and including instructions for controlling said processor,

said processor operative with said instructions in said memory to;

decode said plurality of streamed packets to generate a decoded signal stream;

[[and]]

RESPONSE
SN 09/525,696
PAGE - 8 of 13 -

translate said decoded signal stream into said PCM streamed audio signal; and
rate convert^{ing} said PCM streamed audio signal.

41. (Previously Presented) The apparatus of claim 28 wherein said means for filtering is a low pass filter.

42. (Previously Presented) The apparatus of claim 28 wherein said low pass filter is utilized to prevent aliasing.